

THE EVERKEM EXPERIENCE

Our values, our people, and our products are all part of a much larger commitment to you, something we like to call the Everkem Experience.

The Everkem Experience isn't tangible. It's a state of mind, a way of building partnerships. It's a dedication to doing the small things that others don't, with the deep belief that these little things make the biggest impacts.



QUALITY PRODUCTS



LOW FREIGHT MINIMUM



EXCEPTIONAL SERVICE



SCAN TO VIEW
DIGITAL CATALOG

Manufacturer Rep Agency:

NU-HVAC
SALES

(210) 906-4363
sales@nuhvac.com
San Antonio, TX



120 REGENT DRIVE,
WINSTON-SALEM, NC 27103

FIRESTOPPING | PERFORMANCE SEALANTS | HIGH STRENGTH ADHESIVES | FOAM SEALANTS | ELECTRICAL CHEMICALS
www.everkemproducts.com | 1-800-638-3160



EVERKEMTM
DIVERSIFIED PRODUCTS

**HVAC
PRODUCT LINE**



TRUSIL 100

NSF CERTIFIED 100% SILICONE SEALANT

SPECIFICATIONS

- 100% Silicone
- NSF 51 Certified
- Meets ASTM-C920
- Meets federal specs TT-S-00230C, TT-S-01543A
- Meets FDA Reg No. 21 CFR 177

FEATURES

- +/-25% joint movement
- 50+ Year durability
- High temp performance (up to 400°F)
- Low temperature flexibility (to -55°F)
- Mildew resistant
- Non-sagging
- Low V.O.C.'s
- Available in clear, white, black, & aluminum



Also available in 2.8 oz. squeeze tubes in white and clear



TRUSIL HTS

HI-TEMP SILICONE SEALANT

SPECIFICATIONS

- NSF 51 Certified
- Meets ASTM-C920
- Meets federal specs TT-S-00230C, TT-S-01543A
- Meets FDA Reg No. 21 CFR 177

FEATURES

- High temperature performance
- +/-25% joint movement
- 50+ Year durability
- Exposure up to 600°F
- Low temperature flexibility
- Mildew resistant
- Low V.O.C.'s



FULL-FILL GP

GENERAL PURPOSE GAPS & CRACKS



FEATURES

- Economically insulates, fills, seals
- For use in interior and exterior applications
- Prevents cold air infiltration and heat loss
- Improves energy efficiency
- Adheres to a wide array of common construction materials
- High yield formulation
- Tack free in as little as 10 minutes
- Easy to use

FLAMETECH FB

FIREBLOCKING FOAM



FEATURES

- UL recognized alternative fireblocking material
- For use in Type V residential construction
- Easy to use
- 1 can yields up to 15 tubes of caulk
- Reduces labor costs
- Improves energy efficiency
- Identifiable orange color

FIRE SEAL-136

RESIDENTIAL FIREBLOCKING CAULK



SPECIFICATIONS

- Tested to ASTM-E814 (UL 1479)
- Tested to ASTM-E136
- UL classified

FEATURES

- Great adhesion
- Smooth consistency
- For single family, non-rated penetrations
- Red color
- Low V.O.C.'s

FIRESTOP-814+

INTUMESCENT FIRESTOPPING CAULK

SPECIFICATIONS

- Tested to ASTM-E814 (UL 1479)
- Tested to ASTM-E1966 (UL 2079)
- Meets LEED v4 Emissions requirements (CDPH SM / CA Section 01350)

FEATURES

- Up to a 4 Hour fire rating
- For use in multi-family & commercial construction
- Red color
- CPVC compatible
- Excellent freeze/thaw
- Smooth consistency
- Intumescent
- Elastomeric
- Low V.O.C.'s



Available in 10.1 oz. tubes, 20 oz. sausage tubes, 28 oz. tubes, & 5 gallon pails

FIRE PATCH

FURNACE & RETORT CEMENT

SPECIFICATIONS

- Meets ASTM-C199
- Meets ASTM-E136
- PCE Value 17-18
- Tested to ASTM-C24 Pyrometric Cone Equivalency Test - 2700°F

FEATURES

- Pre-mixed
- Smooth consistency
- Low V.O.C.'s
- Easy cleanup



Available in 1/2 gallon or 1 gallon pails